

## RTZG18SLE

### 18' LEADING EDGE RETRACTABLE - CLASS 2

Ritz Safety Leading Edge Self-Retracting Lifelines are built using a nearly indestructible, high-impact strength polymer housing with a built-in plastic handle and internal aluminum shank and are an ideal choice when working in fall arrest or fall restraint situations. Each SRL features a metal wire guide, 7/32" thick galvanized steel wire rope, steel snap hook, an external shock pack that helps reduce dynamic load impact to less than 1,800 lbs in the event of a fall and swivel anchorage eye with a steel quarter turn-lock carabiner. Taglines are sold separately. This safety harness would be a great choice for a variety of industries such as construction, roofing, mining, general industrial, oil & gas, transportation and utilities.



#### FEATURES

- Made of metal wire guide that lasts longer, improves the SRLs performance and reduce maintenance costs
- Leading Edge Protection with 18 ft. galvanized steel cable with integrated shock absorbers for enhanced safety.
- High-strength, corrosion-resistant materials and high-impact-resistant housing for long-lasting performance.
- Rapid Response Braking System that automatically arrests falls within inches, minimizing injury risk.
- Supports up to 310 lbs., including clothing, tools, and equipment.
- Swivel anchorage connection increases mobility and reduces cable twisting for improved freedom of movement.
- Secure Snap Hook that is self-locking with a large gate opening for easy, secure connection to body harness.
- Built in carrying handle
- Indestructible high-impact strength polymer construction with 7/32" galvanized steel, wire rope

#### TECH SPECS

<b>Wire Guide Material</b>	Metal wire guide
<b>Cable</b>	7/32" Galvanized Steel
<b>Cable Length</b>	18 ft
<b>Lifeline Connector</b>	Steel Snap Hook with Impact Indicator
<b>Anchorage Connector</b>	Steel Swivel Anchorage Eye with Steel Carabiner
<b>Min. Breaking Strength</b>	3400 lbs
<b>ANSI User Capacity</b>	130 lbs - 310 lbs
<b>ANSI SRL Class</b>	CLASS 2
<b>Includes</b>	Steel Twist & Lock Carabiner
<b>Weight</b>	6.95 lbs

#### STANDARDS

Meets or exceeds the applicable industry standards, such as ANSI/ASSP Z359.14-2021 and OSHA requirements, ensuring its quality and performance in fall protection applications.